METHOD AND SYSTEM FOR CONTROLLING VEHICLE DOOR POSITION IN RESPONSE TO DETECTION OF ABNORMAL OPERATION

BACKGROUND OF THE INVENTION

5

1. Field of the Invention

The present invention relates generally motor control systems, and more specifically to a vehicle door control system that detects and responds to abnormal door operation.

10

2. Background of the Invention

Automatic vehicle door opening and closing mechanisms are in widespread use in public transportation systems such as trains and buses, as well as in private vehicles adapted for use by the handicapped. The control of the operation of a vehicle door is typically performed by an electronic control system that determines the position and speed of a moving element of an electric motor that operates the door positioning mechanism. The control system typically stops the electric motor when an abnormality is detected in the operation of the door positioning mechanism by observing position and speed signals from a position detector coupled to the motor and/or positioning mechanism. The control system responds to the detection of the abnormality by removing power from the electric motor in order

1

to prevent breakage of the positioning mechanism, the vehicle door or damage to the electric motor.

Japan Patent Application JP-A-5-344775 discloses a vehicle door control system that provides a signal that is generated when abnormal position or speed of the positioning system is detected. The signal causes the servo motor to stop operating. Japan Patent Application JP-A-5-98867 discloses a vehicle door control system that restricts operation of an electric motor that moves a vehicle door for a predetermined time period when abnormal operation is detected. In both of the systems described in the above-referenced patent applications, the electric motor is ultimately stopped when abnormal operation is detected.

In addition to detecting abnormal door/door positioner operation, indications of continuous abnormal operation in the above-mentioned systems occur when a disconnection or failure of a feedback signal from the position detector occurs and indications of temporary abnormal operation occur when electrical noise is present on the position detector feedback signal(s), such noise due to electrical storms or electrical noise generated by operation of the electric motor. In either case, if the electric motor is controlled in position and speed in conformity with an erroneous feedback signal, the electric

motor, positioning system and/or the vehicle door may be damaged. Therefore, in the above-mentioned control systems, operation of the electric motor is stopped in order to prevent damage.

5

However, stopping operation of a vehicle door control system when no actual possibility of damage exists is undesirable, as delays or complete shutdown prevent the use of the vehicle door and in public transportation applications,

10 prevent persons from entering or exiting the vehicle.

Therefore, it would be desirable to provide a vehicle door control system and method whereby operation of the vehicle door may be continued after detection of an abnormality if a

15 determination is made that the vehicle door control mechanism may be damaged or broken, while preventing operation that may cause damage to the vehicle door, door positioning mechanism or the electric motor.

SUMMARY OF THE INVENTION

The above objectives of providing for continued operation of a vehicle door control system after detection of an abnormality if a determination is made that the vehicle door, positioning system or electric motor will not be damaged is accomplished in a method and system for controlling a vehicle door position.

The system is an electronic control system coupled to an electric motor that operates the vehicle door and is further coupled to an abnormality detector that determines when the position and/or velocity of the door indicates that operation of the door is abnormal. The system further includes a control circuit coupled to the abnormality detector that ceases operation of the electric motor when abnormal operation is detected and resumes operation after a predetermined amount of time has elapsed if the abnormality is no longer present. The control circuit may further include a counter for counting a number of times that operation is resumed and cease resumption of operation if the number of attempts to resume operation exceeds a predetermined count value.

4

When the vehicle door positioning system or the electric motor include a locking device for locking the position of the vehicle door at one or more positions, the control system may further include a locked state detector for detecting that the

5   vehicle door or motor is in one of the locked positions. The control circuit may be coupled to the locked state detector for storing an indication of the locked state position and may compare a position of a next locked state and cease operation of the electric motor if the magnitude of the difference exceeds a

10 predetermined value.

The vehicle door control method is a method of operation of the above-described control system and may be embodied therein.

15 The foregoing and other objectives, features, and advantages of the invention will be apparent from the following, more particular, description of the preferred embodiment of the invention, as illustrated in the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram depicting a vehicle door control system in accordance with an embodiment of the present invention.

Figure 2 is a flowchart depicting a method in accordance with an embodiment of the present invention.

Figure 3 is a flowchart depicting a method in accordance with another embodiment of the present invention.

Figure 4 is a block diagram depicting a vehicle door control system in accordance with yet another embodiment of the present invention.

Figure 5 is a flowchart depicting a method in accordance with yet another embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention is directed toward an electronic control system and method for controlling the position of a

5 vehicle door. The control system operates an electric motor that opens/closes the vehicle door, which may be a public transportation vehicle door such as on a train or bus, or may be an automobile door. The control system includes a detector for detecting the position and/or velocity of door via a detector

10 mechanically coupled to the electric motor. The control system further includes an abnormality detector that determines when the position and/or velocity deviate from an expected position and/or speed. If an abnormality is detected, motor operation is ceased for a predetermined period of time determined by a timer

15 in the control system and then the control system resumes operation of the electric motor if the abnormality detector indicates that the abnormality is no longer present. The control system thereby provides for continued operation when the abnormality is a transient abnormality, e.g., when noise or

20 intermittent operation of the control system causes an indication of an abnormality. The control system also thereby provides for shutdown of the vehicle door positioning system when a continuous abnormality is indicated, e.g., when a disconnection of the motor speed/position feedback signal has

7

occurred. The control system thus provides a means for providing

continued vehicle door operation when there is no possibility of

damaging the door, the electric motor or other portions of the

door positioning mechanism.

5

Referring now to Figure 1, a vehicle door control system **20**

in accordance with an embodiment of the invention is shown.

Control system **20** includes a position calculator **6**, a speed

calculator **7**, an abnormality detector **8**, a driving command

10 calculator **9** and a power converter **10**. Control system **20** is

electrically connected via wiring **12** to a linear motor **2**, which

is mechanically coupled to door **1** in order to open and close

door **1** and further electrically coupled via connection **13** to a

position detector **5** for detecting the position of a moving part

15 of linear motor **2**.

Vehicle door **1** is mechanically connected to the moving part

of the linear motor **2** by a connector **3**, and a locking device **4**

for mechanically fixing door **1** in one or more positions.

20 Position detector **5** detects the position and/or velocity of the

moving part the linear motor **2** and provides detection signals to

position calculator **6**, speed calculator **7** and abnormality

detector **8** via connection **13**. Position calculator **6** calculates

the position of door **1** from the detection signal provided by

8

position detector **5**. Speed calculator **7** also calculates the opening and closing speed of door **1** from the detection signal.

Abnormality detector **8** provides an abnormality detection signal to driving command calculator **9** when an abnormality is detected. An abnormality is indicated by the detected position provided by position calculator **6** and/or speed calculated by speed calculator **7** based on the signals provided by position detector **5** have values that deviate values corresponding to the position and speed control values.

Driving command calculator **9** includes a timer, a serious failure flag, an abnormal state flag and an abnormality start flag and controls the timer and flags, in response to door position information calculated by the position calculator **6**, door speed information calculated by the speed calculator **7** and abnormality indications provided by abnormality detector **8**. Driving command calculator determines driving commands for door **1** thereby controlling power converter **10** for controlling power supplied to linear motor **2**. Power converter 10 supplies power to linear motor **2** in accordance with a power supply command calculated by driving command calculator **9**.

Next, a method for controlling opening closing door **1** as performed by door control system **20** will be described with reference to the flowchart shown in **Figure 2**. First, at step **S1**, driving command calculator **9** determines whether the serious failure flag is set (logical 1) or not (logical 0). If the serious failure flag is set (due to a previous abnormal condition exceeding a predetermined period of time, for example, due of disconnection of electrical connection **13**), then the opening/closing driving of door **1** is stopped at step **S2**. Door **1** is stopped by sending a power supply command to stop the linear motor **2**, which is sent to power converter **10**. Otherwise, if the serious failure flag is not set, then abnormality detector 8 determines whether or not an abnormal condition exists in the position signal provided by position detector **5** (step **S3**). If no abnormality is present, the abnormal state flag is reset to "0" at step **S4**. If there is an abnormality in the detection signal, the abnormal state flag is set to "1" at step **S5**. Then, step S6 determines whether or not the abnormality start flag is set and if not, step **S7** sets the abnormality start flag.

Next, the abnormality start flag is tested at step **S8**. If the abnormality start flag is not set, normal opening/closing of door **1** is continued at step **S9**, by sending a power supply commands sent to power converter **10** that cause linear motor **2** to

10

operate at an opening/closing speed corresponding to the
opening/closing position of door **1**.

If the abnormality start flag is set at step **S8**, a timer is
started at step **S10** and at step **S11** it is determined whether or
not the measured time of the timer has reached a predetermined
time period. If the predetermined time has not been reached,
opening/closing of door **1** is stopped at step **S12**. If the
predetermined time has been reached, the timer is reset (=0) and
the abnormality start flag is reset to "0" at step **S12**. Then,
the abnormal state flag is tested in step **S13**. If the abnormal
state flag is not set, opening/closing operation of door **1** is
continued at step **S9**. However, if the abnormal state flag is
set, the serious failure flag is then set at step **S14** and the
opening/closing of door **1** is stopped at step **S2**.

By the above-described action, in the vehicle control
system of Figure 1, when an abnormality in the detection signal
provided by position detector **5** is detected by abnormality
detector **8**, driving command calculator **9** stops the movement of
door **1**. If the abnormality is still detected after the lapse of
a predetermined time from when the abnormality was initially
detected, the stopped state is maintained. But, if the

abnormality is no longer detected, opening/closing operation of

door **1** is resumed.

Thus, if the abnormality is eliminated after the lapse of a

5   predetermined time, it is determined that the abnormality is a

temporary malfunction of position detector **5** or a minor

transient fault and that there is no possibility of damage or

breakage of linear motor **2** and the devices driven by linear

motor **2**. Therefore, opening/closing operation of the door is

10   resumed and can be continuously carried out. Therefore,

inconvenience due to the fault such as delay in getting on/off a

vehicle and operation of the vehicle can be eliminated in

general.

15   Referring now to **Figure 3**, a flowchart depicting operation

of a vehicle door control system in accordance with another

embodiment of the invention is depicted. Steps corresponding to

the steps in the flowchart shown in Figure 2 are denoted by the

same reference designator and will not be described further in

20   detail, as their operation has been described above. Therefore,

only differences between the embodiment of Figure 3 and the

embodiment of Figure 2 are described below.

12

Driving command calculator **9** is further provided with a
driving resumption counter for counting the number of times the
opening/closing driving of door **1** is resumed. At step **S13**, if
the abnormal state flag is not set, the value of the driving

5 resumption counter is incremented in step **S15**. Then, in step
S16, the driving resumption counter value is compared to a
predetermined threshold count value. If the count is less than
the threshold, opening/closing operation of door **1** is continued
in step **S9**. However, if the operation resumption counter value

10 is greater than or equal to the threshold, the serious failure
flag is set to "1" in step **S14** and opening/closing operation of
door **1** is ceased in step **S2**.

Therefore, according to the above-described embodiment,

15 which can be performed within the system depicted in Figure 1,
driving command calculator **9** includes a counter that counts the
number of times opening/closing operation of door **1** is resumed,
and stops the opening/closing driving control when the count
value reaches a predetermined threshold. If an abnormality is

20 detected in the signal provided by position detector **5** and
operation is thereby ceased for a predetermined number of times,
the method and system determine that the abnormality is not a
temporary malfunction of the position detection means or a
certain minor transient fault but is due to a continuous failure

13

Figure 5. The control is performed in response to the values of the locked state and the locked position as detected by the locked state detector **11**.

5   Referring now to **Figure 5**, a flowchart illustrating operation of a vehicle door control system in accordance with the embodiment depicted in Figure 4 is depicted. Steps corresponding to the steps in the flowchart shown in Figure 3 are denoted by the same reference designator and will not be
10   described further in detail, as their operation has been described above. Therefore, only differences between the method illustrated in Figure 5 and the method illustrated in Figure 3 will be described below.

15   If, it is determined in step **S3** that there is an abnormality indicated by abnormality detector **8**, driving command calculator 9 sets the abnormal state flag to "1" and resets a locked position confirmation flag to "0" in step **S5**. In step **S16**, if the driving resumption counter value is less than the
20   predetermined threshold, then in step **S17** a determination is made whether or not a locked state of the vehicle door has been detected by locked state detector **11**. If a locked state was not detected, opening/closing operation of door **1** is continued at step **S9**.

15

Otherwise, if a locked state was detected and determined in step **S17**, then the locked position confirmation flag is tested in step **S18**. If the locked position confirmation flag is "1", the locked position is stored at step **S19** and the

5   opening/closing operation of door **1** is continued at step **S9**. If, however the locked position confirmation flag is "0" and if, as determined in step **S20**, the absolute value of difference between the previously stored locked position and the locked position as presently indicated by locked state detector **11** is

10   less than a preset range, then the locked position confirmation flag is set to "1". Otherwise, if the locked position confirmation flag was "0" in step **S18**, then the serious failure flag is set to "1" in step **S14** and opening/closing operation of door **1** is stopped at step **S2**.

15

The above-described operation provides for proper operation when a DC offset occurs in the detection signal of position detector **5** so that the detection signal may deviate from the actual detection value. If driving command calculator **9**

20   controls the locking of door **1** by locking device **4** in response to a deviated detection signal, the locked position will be deviated from the original proper position. If the deviation in the locked position increases or frequently occurs, door **1** and devices mechanically coupled to door **1** will be damaged or

broken. Therefore, step **S20** determines whether or not there is
a deviation in the locked position due to a DC offset, and the
opening/closing driving of the door is stopped when there is a
deviation.

5

On the other hand, if the result of the determination in
step **S20** shows that the absolute value of difference is less
than the preset range, there is no deviation in the locked
position or the deviation is within an allowable range.
10 Therefore, the locked position conformation flag is set to "1"
at step **S21** and the locked position is stored at step **S19**. The
opening/closing operation of door **1** is continued at step **S9**.

Thus, the control system of **Figure 4** operating according to
15 the method illustrated in **Figure 3** provides protection against
offset or other deviation in the position detector **5** signal in
order to avoid damage to door **1** or other device mechanically
coupled to door **1**.

20 As an alternative to the above described operation, driving
command calculator **9** may perform the operations of step **S5**,
setting the abnormal state flag to "1" and the locked position
confirmation flag to "0", and may perform the control steps **S17**
to **S21** after step **S13** determines that the abnormal state flag is

17

"0". The above-described alternative order can realize the same effects as those of the third embodiment, performing steps **S15** and **S16** after determination of any locked state, or the resumption counter steps of **S15** and **S16** may be omitted in accordance with another embodiment of the invention that incorporates locked position detection within the embodiment of the invention illustrated in Figure 2.

This application claims the benefit of priority of Japanese application 2003-165424, filed on June 10, 2003, the disclosure of which is incorporated herein by reference.

While the invention has been particularly shown and described with reference to the preferred embodiments thereof, it will be understood by those skilled in the art that the foregoing and other changes in form, and details may be made therein without departing from the spirit and scope of the invention.